



HG Series

Industrial Hot Water Pressure Washers



Providing maximum cleaning power, the stationary HG Series offers the convenience of a steady fuel source, making it the perfect solution for wash bays.

PUMP

- · Factory preset trapping unloader
- Thermal relief valve
- Adjustable high pressure detergent injector

MOTOR

Open drip-proof electric motor with thermal overload protection

FRAME

Powder coated steel side panels and frame

COMPONENTS

- Natural gas or LP gas-fired (vapor only) natural draft with aspirating-type burner, 10-inch stack
- · 24 volt control system
- ¹/₂-inch schedule 80-coil heat exchanger
- Electronic ignition with an intermittent pilot
- Adjustable thermostat

MISCELLANEOUS

 Maximum outlet temperature is 200°F (250°F/121°C outlet temperature with steam option)

UNIT INCLUDES

- Quick connect nozzles 0°, 15°, 25° and 40°
- + 50-foot x $^{\mbox{\tiny 3}\!/}_{\mbox{\tiny 8}}$ -inch steel wire-braided hose
- · Adjustable pressure insulated dual lance with trigger gun

LIMITED WARRANTIES

- · 1 year electric motor
- 3 year coil
- 7 year General pump

CERTIFICATION

· ETL Certified – US and Canada



HG Series Hot Water – Natural Gas/LP – Stationary – Belt Drive

MODEL NUMBER	PSI	GPM	HORSEPOWER/MOTOR	PUMP	NATURAL GAS BTU PER HOUR	LP GAS BTU PER HOUR	DRAFT DIVERTER	DIMENSIONS (LxWxH)	SHIP WT.	NET WT.
HG-3004-1208	3000	3.9	8.0 HP,208V, 1Ø, 40.5A	General	338,000	326,000	21 in.	56.5x29x49.75in.	878 lb.	758 lb.
HG-3004-3208	3000	3.9	8.0 HP,208V, 3Ø, 23.0A	General	338,000	326,000	21 in.	56.5x29x49.75in.	878 lb.	758 lb.
HG-3004-1230	3000	3.9	8.0 HP,230V, 1Ø, 37.0A	General	338,000	326,000	21 in.	56.5x29x49.75in.	878 lb.	758 lb.
HG-3004-3230	3000	3.9	8.0 HP,230V, 3Ø, 20.0A	General	338,000	326,000	21 in.	56.5x29x49.75in.	878 lb.	758 lb.
HG-3004-3460	3000	3.9	8.0 HP,460V, 3Ø, 10.0A	General	338,000	326,000	21 in.	56.5x29x49.75in.	878 lb.	758 lb.

OPTIONS:

PART NUMBER	DESCRIPTION	FITS MODELS
HX-0104	K7 unloader, flow activated (auto start/stop not available) – Converts pressure trapping unloadersystem to flow actuated K7 unloader	All models
HX-0105	Liquid propane (vapor only) – Converts natural gas pressure washer to operate on liquid propane (vapor only)	All models
HX-0106	Hour meter – Displays the number of hours unit has been in operation	All models
HX-0107	Time delay shutdown - Timer will shut unit off automatically when trigger gun is released and timer reaches setting	All models
HX-0108	(1) Remote station (auto start/stop not available), plastic control box – Addsplastic control box with rocker switches, can be mounted away from unit to control on/off, burner and scap injection	All models
HX-0109	Time delay shutdown and first remote, plastic control box—Timer will shut unit off automatically whentrigger gun is released and timer reachessetting; adds plastic control box with rocker switches, can be mounted awayfrom unit to control on/off, burner and soap injection	All models
HX-0110	Additional remotes (up to 3), plastic control box – Additional plastic control boxes with rocker switches, can be added to unit after the first remote is installed; requires HX-0108 or HX-0124 option	All models
HX-0111	Auto start/stop – Whentrigger gun is released, the timer will turn unit off; when trigger gun is pulled, unit will restart	All models
HX-0121	250°F steam – Increases outlet temperature to 250°F while lowering system pressure; adds re-sized 25° nozzle to be used as steam nozzle	All models
HX-0124	Auto start/stop and first remote, plastic control box – Whentrigger gun is released timer will turn unit off, when trigger gun is pulled, unit will restart; adds plastic control box with rocker switches, can be mounted away from unit to control on/off, burner and soap injection	All models
HX-0288	(1) Remote station (auto start/stop not available), metal control box – Addsplastic control box with rocker switches, can be mountedawayfrom unit to control on/off, burner and soap injection	All models
HX-0289	Time delay shutdown and first remote, metal control box – Timer will shut unit off automatically when trigger gun is released and timer reachessetting; adds metal control box with rocker switches, can be mounted awayfrom unit to control on/off, burner and soap injection	All models
HX-0290	Additional remotes (up to 3), metal control box - Additional metal control boxes with rocker switches, can be addedto unit after the first remote is installed	All models
HX-0296	Programmable logic controller (PLC)- Includes auto start/stop and timed lockout	All models
HX-0297	Programmablelogic controller with first remote, plastic control box – Includes auto start/stop and timed lockout	All models
HX-0299	Auto start/stop and first remote, metal control box – Whentrigger gun is released timer will turn unit off, whentrigger gun is pulled, unit will restart; adds metal control box with push-buttons, can be mounted away from unit to control on/off, burner and scap injection	All models
HX-0304	Programmablelogic controller with first remote, metal control box - Includes auto start/stop and timed lockout	All models
HX-0305	Additional programmable logic controller remotes, plastic control box – Addsadditional remotesto PLC	All models
HX-0306	Additional programmable logic controller remotes, metal control box – Adds additional remotesto PLC	All models

Note: Youcannot order HX-0107 and HX-0108 together, you will need to order HX-0109 instead. HX-0107 and HX-0108 can be ordered separately.

