



Hot Water Mini Trailers

Trailer-Mount
Pressure Washers

Belt Drive — Gasoline



Easy to tow from one job to the next, this trailer offers the convenience of portable cleaning. Equipped with a 12V Beckett burner, this trailer is ideal for heavy-duty cleaning.



HMT-4004-0MGH shown with adjustable trailer coupler hitch, TX-0010



Hot Water Mini Trailers

Trailer-Mount Pressure Washers – Belt Drive – Gasoline

PUMP

- Adjustable stainless-steel and brass unloader valve
- Forged brass manifold
- Thermal relief valve

ENGINE

- Remote engine start and choke
- 12V electric start – battery not included

FRAME

- Reinforced powder coated steel frame
- Locking rear storage area – 2.875 cubic feet
- Sealed LED trailer lights
- 2-inch ball hitch
- Caster brake (Use when unhitched)
- (2) 4.80-8 8-inch bias ply tires

COMPONENTS

- ½-inch schedule 80 pipe-coil with 4-pancake heat exchanger
- 12V Beckett burner
- No. 1 or No. 2 fuel oil, diesel or kerosene fired burner (Not approved for bio-fuel)
- Engine hour meter
- 1,000-lb. axle

MISCELLANEOUS

- Temperature rise 140°F/60°C above ambient

SAFETY FEATURES

- Removable safety flag for transportation and guidance when backing up
- Recommended maximum speed is 65 mph
- DOT approved
- 250°F high temperature safety limit switch

UNIT INCLUDES

- Quick connect nozzles – 0°, 15°, 25° and 40°
- 50-foot x ¾-inch steel wire-braided high pressure hose
- Professional-grade insulated trigger gun with safety lock-off
- Adjustable pressure insulated dual lance

LIMITED WARRANTIES

- 3 year engine
- 7 year pump

MODEL NUMBER	PSI	GPM	DISPLACEMENT/ENGINE	PUMP	ENGINE FUEL TANK CAP.	BURNER FUEL TANK CAP.	BURNER FUEL CONS.	BTU PER HOUR	DIMENSIONS (LxWxH)	GROSS VEHICLE WT.
HMT-4004-OMGH	4000	3.7	389cc Honda GX390 OHV*	General	1.61 gallons	10.0 gallons	2.45 gph	343,000	99x43.5x36in.	1,000 lb.
HMT-4004-OMGV	4000	3.7	408cc Vanguard OHV	General	1.61 gallons	10.0 gallons	2.45 gph	343,000	99x43.5x36in.	1,000 lb.

Note: All gasoline models sold in California are required to have a CARB compliant engine. Consult factory.

*49 state engine. Not for sale in California.

ACCESSORIES:

PART NUMBER	DESCRIPTION	FITS MODELS
15-0160	75-foot x ¾-inch hose – 4500-PSI rated, R2, for use with hose reel, TX-0020	All models
15-0161	100-foot x ¾-inch hose – 4500-PSI rated, R2, for use with hose reel, TX-0020	All models
20-1366A52	Black powder coated rain cap – Protects boiler from moisture build-up when unit is left outside, octagonal	All models
AW-8400-0021	Low pressure detergent injector – Allows the user to apply the recommended detergents	All models

OPTIONS:

PART NUMBER	DESCRIPTION	FITS MODELS
TX-0010	Adjustable trailer coupler hitch – Replaces the standard 2-inch ball hitch with a 2-inch trailer hitch with pin-style fastener trailer coupler and hinged ball socket	All models
TX-0020	High pressure hose reel – 12-inch hose reel, 100-foot maximum hose length	All models



Rear Storage Area



WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov.