



Build Your Own

Single and Dual-Axle Trailers

Customizable with Industrial Pressure Washers

AW-9000-0005 single-axle trailer shown with HVS-3505-1H6G hot water pressure washer, hose reels and industrial water supply hose, 15-0006 (Available as accessories)

These trailers are ideal for cleaning at remote jobsites. Customize a single or dual-axle trailer with an industrial pressure washer, hose reel and accessories to fit your job requirements.



Build Your Own Single and Dual-Axle Trailers

STEP 1: Pick a single or dual-axle trailer

SINGLE-AXLE TRAILERS

MODEL NUMBER	WATER TANK	BRAKES	TIRES	AXLE	DIMENSIONS (LxWxH)	GROSS VEHICLE WT.
AW-9000-0005	(1)200-gallon	Surge	(2) ST205-75R15in. radial	(1) 3,500 lb.	13.2x6.8x5.6ft.	3,500 lb.
AW-9000-0006	(1)200-gallon	Electric	(2) ST205-75R15in. radial	(1) 3,500 lb.	13.2x6.8x5.6ft.	3,500 lb.
AW-9000-0007	(1)200-gallon	None	(2) ST205-75R15in. radial	(1) 3,500 lb.	13.2x6.8x5.6ft.	3,500 lb.

DUAL-AXLE TRAILERS

MODEL NUMBER	WATER TANK	BRAKES	TIRES	AXLE	STORAGE AREA	DIMENSIONS (LxWxH)	GROSS VEHICLE WT.
AW-9000-0003	(2) 200-gallon	Surge	(4) ST205-75R15in.	(2) 3,500 lb.	5ft.x4ft.x12in.	13.2x6.8x5.6ft.	7,000 lb.
AW-9000-0004	(2) 200-gallon	Electric	(4) ST205-75R15in.	(2) 3,500 lb.	5ft.x4ft.x12in.	13.2x6.8x5.6ft.	7,000 lb.
AW-9000-0008	(1)200-gallon	Surge	(4) ST205-75R15in.	(2) 3,500 lb.	None	13.2x6.8x5.6ft.	7,000 lb.

STEP 2: Pick your trailer accessories and options

HOSE REELS

High Pressure Hose Reels

These high pressure hose reels include a jumper hose and mounting bracket.

TX-0001 13-inch reel

TX-0002 16-inch reel

Dual High Pressure and Single Low Pressure Hose Reels

Includes mounting brackets, plumbing and jumper hoses for two high pressure hose reels and one low

pressure hose reel.

TX-0023 16-inch reels

Low Pressure Hose Reels

These low pressure hose reels include a mounting bracket and plumbing.

TX-0003 16-inch reel for use with AW-9000-0003 and AW-9000-0004 trailers

TX-0013 16-inch reel for use with AW-9000-0005m AW-9000-0006, AW-9000-0007 and AW-9000-0008 trailers Replacement Hose Reel Parts

When adding hose reels to single or dual-axle trailers, use the following jumper hose and mounting brackets. 15-0159 40-inch x ³/₈-inch jumper hose, black, 4500-PSI

13-0179A18 Mounting bracket, low pressure hose reel/single high pressure reel

13-0258A18 Mounting bracket, dual high pressure reels

50-0195 13-inch hose reel, 150-foot maximum hose length, rated for units up to 4000-PSI

50-0196 16-inch hose reel, 200-foot maximum hose length, rated for units up to 4000-PSI

TANK DRAINS

Single Tank Drain

This tank drain includes a valve and drain hose for trailers equipped with a single 200-gallon water tank. TX-0021 Tank drain for use with AW-9000-0005, AW-9000-0006, AW-9000-0007 and AW-9000-0008 trailers **Duan Tank Drain**

This tank drain includes valves and drain hoses for trailers equipped with two 200-gallon water tank. TX-0022 Tank drain for use with AW-9000-0003 and AW-9000-0004 trailers

TRAILER HITCHES

Replaces the standard 2-inch ball hitch with an adjustable trailer coupler hitch or lunette ring hitch. Includes hitch with brackets and hardware.

TX-0009 Adjustable trailer coupler hitch for AW-9000-0004, AW-9000-0006 and AW-9000-0007 trailers

TX-0010 Adjustable trailer coupler hitch for AW-9000-0003, AW-9000-0005 and AW-9000-0008 trailers

- Heavy-duty 2-inch trailer hitch with pin-style fastener trailer coupler and hinged ball socket with visual indication of proper closure around

- the ball all to ensure a quick, easy and secure hook-up
- TX-0018 Lunette ring hitch for AW-9000-0006 and AW-9000-0007 trailers
- TX-0019 Lunette ring hitch for AW-9000-0003, AW-9000-0004 and AW-9000-0008 trailers
- 3-inch integrated lunette ring for use with pintle hitches





A WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov.

STEP 3: Pick your pressure washer and options

Choose a cold or hot water belt-driven pressure washer for your cleaning needs. Consult factory for skid prep options and additional pressure washer options available.

SINGLE & DUAL-AXLE TRAILER FEATURES

- Jack with pad
- · 2-inch ball hitch
- · Rubber mounted sealed lights
- Tanks are enclosed in a powder coated steel frame
- · Will fit all Mi-T-M belt-driven pressure washers*
- . 3/16-inch solid steel trailer deck plate
- · Storage area located under the water tanks (AW-9000-0003 and AW-9000-0004 trailers)
- (2) 200-gallon water tanks plumbed together (AW-9000-0003 and AW-9000-0004 trailers)
- Backflow preventers
- Trailer tank bypass
- *Pressure washers sold separately.