



ULTRATECH
INTERNATIONAL, INC

Sold by
ONE
CLARION

SPCC

MADE IN
USA

Product Data Sheet

Ultra-Berm Builder Plus

Drive-over barrier provides heavy-duty custom containment

- + Create permanent containment on concrete, asphalt and most sealed areas.
- + Heavy-duty, 40-ounce, vinyl-coated fabric can withstand traffic from trucks, forklifts and other vehicles.
- + Open-cell foam core compresses to approximately 1/4" when driven over and springs back to shape when vehicles pass.
- + Secures to the floor with sealant (not included) and is reinforced with pre drilled aluminum mounting strips (included) and steel anchors (included).
- + Can be used with standard Ultra-Berm Builder.



Part#	Description	Dimensions in. (mm)	Qty	Weight lbs. (kg)
2" Model				
8671	Straight Section	150 x 5.5 x 2 (3,810 x 139.7 x 50.8)	1/box	11.50 (5.22)
8672	Corner	11 x 5.5 x 2 (279.4 x 139.7 x 50.8)	2/box	2.0 (0.9)
8673	Wall End	8 x 5.5 x 5 (203.2 x 139.7 x 127)	2/box	2.0 (0.9)
4" Model				
8634	Straight Section	144 x 6 x 4 (3657.6 x 152.4 x 101.6)	1/box	14.0 (6.4)
8635	Corner	12 x 6 x 4 (304.8 x 152.4 x 101.6)	2/box	4.0 (1.8)
8636	Wall End	7 x 6 x 4 (177.8 x 152.4 x 101.6)	2/box	3.0 (1.4)
6" Model				
8637	Straight Section	144 x 8 x 6 (3657.6 x 203.2 x 152.4)	1/box	21.0 (9.5)
8638	Corner	15 x 8 x 6 (381 x 203.2 x 152.4)	2/box	7.0 (3.2)
8639	Wall End	7 x 8 x 6 (177.8 x 203.2 x 152.4)	2/box	9.0 (4.1)
Options				
8644	Floor Sealant (10.3 fl. oz. tube)	N/A	6/box	8.0 (3.5)
8645	Vinyl Adhesive (8 oz. can)	N/A	1/box	1.0 (0.5)

Continued on the next page

Material Specifications

Base Fabric (100% Polyester)	1300D x 1300D / 31 x 31
Weight (FS-191-5041)	40 oz./yd ²
Tensile Strength (Grab) (FS-191-5100)	920 lbs x 870 lbs
Tensile Strength (Strip) (FS-191-5102)	685 lbs x 655 lbs
Tear Strength (Tongue) (FS-191-5134)	715 lbs x 695 lbs
Adhesion Strength (FS-191-5970)	11 x 11 lbs / inch
Abrasion Resistance (FS-191-5306)	685 cycles
Hydrostatic Resistance (FS-191-5512)	At least 600 lbs / inch ²
U.V. Resistance (Weather-O-Meter)	Not excessive fading after 300 HRS
Cold Crack Resistance (FS-191-5874)	-40° F
High Temperature Resistance (FS-191-5872)	180° F (Does not Block)