

Ultra-Drain Plugs® Product Data Sheet



Part number: 2113/2114/2115/2117/2118/2119/2121/2116

Material Specifications

Specification	Value	
Style	Cone	
Color	Safety Orange	
Intended for	Floor Drains	
Max Liquid Temp Exposure	225 °F for up to 30 mins	107.2 °C for up to 30 mins
Storage Temp Range	0°- 120°F	-17.7 ° - 48.8 °C
Temperature Limit	0 °- 160 °F	-17.7 °- 71.1 °C
Sold As	1 Each	
Composition	Polyurethane	

Description: A non-absorbing urethane plug that forms a temporary bond with drain walls to stop leaks from entering the drain.

Application: For use in response to machine leaks and small chemi- cal spills. They can be quickl deployed to plug floor or storm drains until the spill or leak can be cleaned in accordance with local and state regulations.

Product Features: The Ultra-Drain Plug is an essential part of your spill response kit that can be quickly deployed to plug drains and prevent spills or leaks from going down the drain.

- + Tapered design wedges securely into standard drains to stop any flow.
- + Eye bolts are removable, allowing installation of grating with Drain Plug in place.
- + Non-absorbing, easily cleaned for repeated use.
- + Flexible polyurethane material resists oil, water and most aggressive chemicals.
- + Cleans with soap and water.

Composition: 100% polyurethane surrounding solid substrate core.





Part#	Color	Miscellaneous Features	Qty	Top Diameter	Bottom Diameter	Weight
2113	Safety Orange		1	2.5" (63.5mm)	1.5" (38mm)	2 lbs (1kg)
2114	Safety Orange		1	3.5" (89mm)	2.5" (63.5mm)	2 lbs (1kg)
2115	Safety Orange		1	4.5" (114mm)	3.5" (89mm)	3 lbs (1.5kg)
2117	Safety Orange		1	7" (178mm)	5" (127mm)	6 lbs (3kg)
2118	Safety Orange		1	9" (228mm)	6.5" (165mm)	13 lbs (6kg)
2119	Safety Orange		1	11.5" (292mm)	8" (203mm)	16 lbs (7.5kg)
2121	Safety Orange		1	13.5" (343mm)	10" (254mm)	25 lbs (11 kg)
				Imperial	Metric	
2116	Safety Orange	3 Plug Kit (2", 3", 4" Drain Plugs) w/Plastic Carrying Case	1	15"x11.5"x6"	381mm x 292mm x 153mm	8 lbs (3.5kg)