

Product Data Sheet



Item Number: 1057 / 1058

Item Name: Ultra-IBC Spill Pallet

Load Capacity UDL

- 16,000 lbs./each (7,273 kg/each)

Sump Capacity

- 400 gal./each (1,514 L/each)

Options Available

Item	Size	Color	Misc. Features	Amount	Length	Width	Height	Depth	Weight
1057	—	Yellow	No Drain	1 each	58.75" (1,492 mm)	58.75" (1,492m m)	33" (838 mm)	—	444 lbs. (202 kg)
1058	—	Yellow	With Drain	1 each	58.75" (1,492 mm)	58.75" (1,492m m)	33" (838 mm)	—	444 lbs. (202 kg)

Color: Yellow and Black

Per Pallet: 1

Description

Our strongest Containment Unit holds up to 6 tons so you can stack two IBCs and save floor space.

Product Features

- 4"-thick, two-section decking is supported by all-poly inner pedestals for superior load handling
- Heavy-duty construction permits long-term stacked storage of two IBCs to save space
- Low-density polyethylene (LDPE) construction resists UV rays, rust, corrosion and most chemicals
- Textured grating holds a variety of IBC sizes; if tank has feet or pegs, be sure to use proper support pads or plates

- Translucent yellow sidewalls allow easy visual inspection
- Positioning pegs in pedestals keep deck from shifting
- Arrives ready to use with no assembly required

Composition

- Sump - Polyethylene
- Grates - Injection Molded Polyethylene

This product helps you comply with:

40 CFR 264.175 - Hazardous waste containment systems must be free of structural cracks or gaps, be designed to keep spilled liquids from remaining in contact with the container, prevent run-on and "have sufficient capacity to contain 10% of the volume of the containers, or the volume of the largest container, whichever is greater."

40 CFR 122.26 - When applying for a National Pollutant Discharge Elimination System (NPDES) permit, facilities must have a plan in place that describes actions, procedures, control techniques, management practices and equipment available to prevent illegal discharge of pollutants into waterways.

40 CFR 112.7 - SPCC planning requirements state that facilities subject to these regulations must have written plans in place discussing the products, countermeasures and procedures that are in place, or will be taken by the facility to prevent discharge of oil into waters of the United States.

Additional Specifications

- ☐ Fork Truck Access: N/A
- ☐ Grates: Two 52" L x 26" W
- ☐ Recycled Content: 18% Post-Industrial Recycled Polyethylene

Disclaimers

- ☐ **Notice:** Call Technical Services at 1-800-353-1611 or visit our website at SpillContainment.com for chemical compatibility.