

Ultra-Containment Berm® Economy Model



Economical L-shaped wire bracket berm design offers cost savings and secure spill containment

- + L-shaped wire brackets provide sturdy sidewall support.
- + 12” sidewall contains spills in drilling and fracking locations.
- + No frames, components or excess material outside of sidewalls — excellent for use as spill containment area inside of storage sheds and other buildings or structures where floor space is a premium.
- + Standard material of construction is 30 mil reinforced polyethylene. Other materials available upon request.
- + **Meets SPCC and EPA Container Storage Regulations 40 CFR 264.175.**



Rugged polyethylene material can withstand a variety of containment needs.



Part#	Dimensions ft. (m) Wall Height: 12 in. (305 mm)	Containment Capacity gal. (L)	Weight lbs. (kg)
8240	6 x 6 (1.9 x 1.9)	269 (1018.28)	9.0 (4.1)
8241	10 x 10 (3.05 x 3.05)	748 (2831.49)	23.0 (10.4)
8242	12 x 12 (3.65 x 3.65)	1077 (4076.88)	29.0 (13.2)
8243	12 x 25 (3.65 x 7.62)	2244 (8494.464)	49.0 (22.2)
8244	10 x 50 (3.65 x 15.24)	3740 (14157.44)	84.0 (38.1)
8245	12 x 50 (3.65 x 15.24)	4488 (1695.86)	88.0 (40.0)

*Custom sizes available upon request.



ULTRATECH
INTERNATIONAL, INC.

Part#	Dimensions ft. (m) Wall Height: 12 in. (305 mm)	Containment Capacity gal. (L)	Weight lbs. (kg)
2858	4 x 4 x 1 (1.2 x 1.2)	119 (450.46)	8 (3.63)
2859	6 x 4 x 1 (1.8 x 1.2)	179 (677.59)	10 (4.54)
2860	8 x 6 x 1 (2.4 x 1.8)	359 (1359)	13 (5.9)
2861	8 x 8 x 1 (2.4 x 2.4)	478 (1809.43)	17 (7.71)
2862	20 x 10 x 1 (6.1 x 3)	1496 (5663)	50 (22.68)
2863	30 x 10 x 1 (9.1 x 3)	2244 (8494.46)	53 (24.04)
2864	40 x 10 x 1 (12.2 x 3)	2992 (11326)	67 (30.39)
2865	20 x 12 x 1 (6.1 x 3.7)	1795 (6794.81)	43 (19.50)
2866	30 x 12 x 1 (9.1 x 3.7)	2692 (10190.33)	59 (26.76)
2867	40 x 12 x 1 (12.2 x 3.7)	3590 (13589.63)	74 (33.57)
2868	60 x 12 x 1 (18.3 x 3.7)	5385 (20384.44)	105 (47.63)
2869	50 x 15 x 1 (15.2 x 4.6)	5610 (21236.16)	132 (59.87)
2870	60 x 15 x 1 (18.3 x 4.6)	6732 (25483.39)	151 (68.49)

*Custom sizes available upon request.