

- + Heavy-duty, 30 mil, textured polyethylene liner provides rugged, impermeable barrier to capture leaks and spills.
- + Creates large, semi-permanent containment areas. Provides much more gallon capacity than shorter walled containment systems.
- + Versatile system can be easily disassembled for reuse at future sites.
- + Unlike some containment systems, the Ultra-Containment Wall is not secured to the substrate so it is perfect use in parking lots, sand, rocky soil, muddy soil, frozen soil or on concrete areas.
- + Made in the USA.

8885

3 (0.9)

+ Meets SPCC, EPA Container Storage Regulation 40 CFR 264.175.

15 x 55.7 x 3 (4.6 x 17 x 0.9)



Connector pins allow systems to be setup quickly and easily without the need for special tools or equipment.



Large clips (included) hold the liner in place. Excess liner can be trimmed if desired.

3,007.5 (1,364.2)

36 (914)

Part#	Wall Height & Description ft. (m)		Dimensions in. (mm)	Weight lbs. (kg)	Max. Fill	Height in. (mm)
8896	1 (0.3) - Straight Section		86 x 18 x 12 (2,184.4 x 457.2 x 304.8)	34 (15.4)	12 (305)	
8897	1 (0.3) - Corner Section		36.8 x 36.8 x 12 (933.5 x 933.5 x 304.8)	12 (5.4)	12 (305)	
8880	2 (0.6) - Straight Section		86 x 24 x 24 (2,184.4 x 609.6 x 609.6)	65 (29.5)	24 (610)	
8881	2 (0.6) - Corner Section		36.8 x 19 x 24 (933.5 x 483.6 x 609.6)	19 (8.6)	24 (610)	
8883	3 (0.9) - Straight Section		86 x 24 x 36 (2,184.4 x 609.6 x 914.4)	76 (34.5)	36 (914)	
8884	3 (0.9) - Corner Section		36.8 x 19 x 36 (933.5 x 483.6 x 914.4)	25 (11.3)	36 (914)	
Complete Systems:						
Part#	Wall Height ft. (m)	Usable Dimensions ft. (m) Item Quantity	Containment Cap. gal. (L)	Weight lbs. (kg)	Max. Fill Height in. (mm)
8898	1 (0.3)	15 x 55.7 x 1 (4.6 x 16.8 x 0.3)	20-Straight, 4-Corners, Liner not included	6,211 (23,511.2)	728 (330)	12 (305)
8882	2 (0.6)	15 x 55.7 x 2 (4.6 x 17 x 0.6)	20-Straight, 4-Corners, Liner not included	12,421 (47,018.6)	1,376 (624)	24 (610)

20-Straight, 4-Corners, Liner not included 18,632 (70,529.8)