



ULTRATECH
INTERNATIONAL, INC

Ultra-Sidewinder, Medium Specifications

Sold by:
ONE
CLARION

Part#	1830, 1831, 1832, 1833
Dimensions In. (mm)	System: 33 x 9¾ x 1⅜ (838 x 248 x 35) Extension: 14⅛ x 9¾ x 1⅜ (358 x 248 x 35)
Weight	System with endcaps: 6.0 (2.7) Extension: 2.0 (0.9)
Load Capacity	260 lbs./in2 (18.3 kg./cm2)
Load Capacity per axle:	13,500 lbs. (6,123 kg.)
Construction	Injection-molded acrylonitrile butadiene styrene (ABS) plastic and injection-molded Santoprene™ vulcanized rubber tabs
Internal channel opening	3"W x 3/4"H (76mm x 19mm)
Operating Temp.	-40°F to 120°F (-40°C to 49°C)

- Systems include two (2) end caps. Extensions can be added for increased system length (end caps are not included with extensions). Segments can be removed to create custom lengths.
- Modular design allows for easy reconfiguration or repair, even with the cable or cord in place.
- Unit is designed for office and light-industrial use and is designed to be run on flat, stable surfaces. Not intended to span gaps, holes or trenches with any weight load.
- The system is capable of withstanding loads from vehicles with pneumatic tires but not designed to be run over by any equipment or vehicle with rigid wheels.

